

## Lightning Rod Air Termination



Part No.	Rod Length (L) (mm)	Rod Diameter (Ø) (mm)	Thread (mm)	Weight (kg)
S-SLRC 58-30	300	15	5/8	0.50
S-SRLC 58-50	500	15	5/8	0.80
S-SRLC 58-60	600	15	5/8	0.96
S-SRLC 58-100	1000	15	5/8	1.60
S-SRLC 58-150	1500	15	5/8	2.40
S-SRLC 58-200	2000	15	5/8	3.20
S-SRLC 34-30	300	19	3/4	0.75
S-SRLC 34-50	500	19	3/4	1.20
S-SRLC 34-60	600	19	3/4	1.51
S-SRLC 34-100	1000	19	3/4	2.50
S-SRLC 34-150	1500	19	3/4	3.80
S-SRLC 34-200	2000	19	3/4	5.00

The Lightning Rod only use raw materials from LME Grade A. Highlights of Oxygen Free. Features durable bending. Can bring electricity as well.

Designed by international standards.

- JIS H3140 , JIS H3250 C1020 (CU OF-OKTM 99.99%)
- ASTM B170-82-grade
- UK BS 1981 Cu-OF
- DIN 1787 OF-CU
- TIS 408-2553

