


Automatic Transfer Switch (ATS)



Features

Product overview

Dual power automatic switch is a newly developed micro household whether the main power supply or standby power is normal. When the normal power supply is abnormal, the standby power supply will immediately start to work, to ensure the continuity, reliability and safety of the power supply. This product is specially designed for domestic track installation and is specially used for PZ30 distribution box.

Dual power automatic switch is suitable for 50 or 60HZ rated 400V AC emergency power supply system. ATS has the characteristics of solid structure, reliable conversion, easy installation and maintenance and long life. It is widely used in a variety of occasions when can not sustain power failure, that is, reliable electrical work, but also manual operation. ATS is made up of TSE and controller. According to GB/T14048.11, makes part 6-1: multi-function equipment and switching equipment, ATS is the most suitable low-voltage switching equipment and control device. power

Technical Data

Model No.	S-PV-ATS-2P-100A	S-PV-ATS-4P-125A
Rated current Ie A	32 , 40 , 50 , 63 , 100 A	80 , 100 , 125 A
Insulation voltage Ui	AC690V,50Hz	
Rated voltage Ue	AG400V,50Hz	
Level	PC can be manufactured and sustained , without short	
Using categories	AC-33Ib	AC-31B
Rod	2P	4P
Electrical appliances	Life; 2000times; manual operation: 5000 times	
Rated short charge	50kA	
Short circuit	RT 16-00-63A	
The cap withstands	8kV	
Control circuit	Rated control voltage Us: AC220V,	85%Us-110%Us
Auxiliary circuit	Two relays, each with two sets of contact capacity for the contact converter: AC220V50Hz Ie=5y	
Contactor conversion	<50ms	
Operation	<50ms	
Return conversion	<50ms	
Power off time	<50ms	
Weight (kg)	0.4 kg.	0.6 kg.

Ordering information		
Model No.	S-PV-ATS-2P-100A	S-PV-ATS-4P-125A
Part No.	660302	660303
Warranty	1 year from Delivery date	
Packing unit.	1 pc(s).	

Contact us

You can find the address of your local sales organisation on the home page



www.sefco.co.th



www.sefco23.com



LINE



Facebook



WeChat



WhatsApp

SEFCO - Tel. : +66 (0) 3811 9780-2

SEFCO - Fax. : +66 (0) 38 119 783